

ROCK STAR (SB SPL) - Technical Specifications



Description

ROCK STAR has been specially designed for equipment being used both on the road and on steel rails. ROCK STAR is a 32-ply-rated tire for outstanding load capacity. The unique tread compound provides superior cut and chip resistance and steel belts stand for durability.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Road Rail Equipment

Version	STEEL BELTED SPL
Type	TL
Tyre Size	14.00 - 24

Dimensions US Standard

Usa code	94057177
Ply Rating	32
Overall Width (inch)	15.4
Overall Diameter (inch)	56.1
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	31250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/22/2025 5:27 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..