



## RT 853 - Data Sheet



### Description

RT 853 is a R-1 tire for tractors and vineyard harvesters in soil tillage and vineyard harvesting applications. It features great traction, load capacity and self-cleaning properties.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agriculture: Tractor • Vineyard Harvester

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>480/80 R 38 (18.4 R 38)</b>	STANDARD	R1	149 A8/B	W 16 L	W 15 L ; W 14 L	475	1747	793	5300	825	TL	E4-106R-001822
<b>520/85 R 38 (20.8 R 38)</b>	STANDARD	R1	155 A8/B	DW 16 L	DW 18 L ; DD 16 L	516	1849	830	5592	875	TL	E4-106R-001483

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 7:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..