

RT 857 - Technical Specifications



Description

RT 857 is a tire designed for soil tillage applications. Its strong casing offers excellent durability and traction. The stubble-resistant tread compound features high cut-and-chip resistance.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	340/85 R 28 (13.6 R 28)
LI/SS	127 A8/B

Dimensions US Standard

Usa code	94041916
Section Width (inch)	13.9
Overall Diameter (inch)	50.7
Static Loaded Radius (inch)	23.6
Rolling Circumference (inch)	153.9
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000759
TRA Code	R1

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2130	2470	2820	3160	3520	3860
25	2130	2470	2820	3160	3520	3860
20	2280	2650	3020	3390	3770	4130
5 LT	2840	3320	3780	4240	4710	5170
5 HT	2280	2650	3020	3390	3770	4130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 3:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..