

# **RT 857 - Technical Specifications**



## **Description**

RT 857 is a tire designed for soil tillage applications. Its strong casing offers excellent durability and traction. The stubble-resistant tread compound features high cut-and-chip resistance.

#### **UM**

**US Standard** 

#### Construction



## Machinery

Agriculture: Tractor

Version	STANDARD
Туре	TL
Tyre Size	380/85 R 28 (14.9 R 28)
LI/SS	133 A8/B

### **Dimensions US Standard**

Usa code	94042241
Section Width (inch)	15.4
Overall Diameter (inch)	53.4
Static Loaded Radius (inch)	24.3
Rolling Circumference (inch)	162.5
Rim Rec	W 12
Rim Alt	W 11; W 13
ECE	E4-106R-000769
TRA Code	R1

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2500	2910	3320	3730	4130	4540
25	2500	2910	3320	3730	4130	4540
20	2680	3120	3550	3990	4430	4860
5 LT	3360	3900	4450	5000	5560	6100
5 HT	2680	3120	3550	3990	4430	4860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 5/1/2025 12:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..