



RT 857 - Data Sheet



Description

RT 857 is a tire designed for soil tillage applications. Its strong casing offers excellent durability and traction. The stubble-resistant tread compound features high cut-and-chip resistance.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Tractor

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
320/85 R 24 (12.4 R 24)	STANDARD	94052318	R1	122 A8/B	W 11	W 10 ; W 9	13	45.4	20.8	135.8	TL	E11-106R-002976
380/85 R 24 (14.9 R 24)	STANDARD	94053773	R1	131 A8/B	W 12	W 13 ; W 11	15	49.4	22.3	148.9	TL	E11-106R-002977
420/85 R 26 (16.9 R 26)	STANDARD	94045013	R1	138 A8/B	DW 15 L	W 14 L ; W 15 L ; W 16 L ; DW 16 L	17.7	54.1	24.3	162	TL	E11-106R-003471
460/85 R 26 (18.4 R 26)	STANDARD	94045624	R1	143 A8/B	DW 15 L	W 15 L ; W 16 L ; DW 16 L	18.3	56.8	25.3	169.2	TL	E4-106R-001479
320/85 R 28 (12.4 R 28)	STANDARD	94041923	R1	124 A8/B	W 11	W 9 ; W 10	13	49.4	22.7	148.8	TL	E4-106R-000757
340/85 R 28 (13.6 R 28)	STANDARD	94041916	R1	127 A8/B	W 12	W 11	13.9	50.7	23.6	153.9	TL	E4-106R-000759
380/85 R 28 (14.9 R 28)	STANDARD	94042241	R1	133 A8/B	W 12	W 11 ; W 13	15.4	53.4	24.3	162.5	TL	E4-106R-000769
420/85 R 28 (16.9 R 28)	STANDARD	94042258	R1	139 A8/B	W 15 L	W 14 L ; W 13	17.7	56.1	25.2	168.3	TL	E4-106R-000770
420/85 R 30 (16.9 R 30)	STANDARD	94044566	R1	140 A8/B	W 15 L	W 14 L ; W 13	17.7	58.1	25.8	173.1	TL	E4-106R-001394
460/85 R 30 (18.4 R 30)	STANDARD	94045020	R1	145 A8/B	W 16 L	W 15 L ; W 14 L	18.7	60.8	27.4	183	TL	E4-106R-001480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 8:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..