

SAND KING - Data Sheet



Description

SAND KING is a block pattern tire specially designed for trailers in transport applications. It provides excellent traction on sandy surfaces and best ground contact.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Trailer

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
7.50 - 16	STANDARD	12	5.50 F SDC	6.00 G	215	820	378	2471	TT	
7.50 - 16	STANDARD	8	5.50 F SDC	6.00 G	215	820	378	2471	TT	E4-54R-0022810
7.50 - 16	STANDARD	10	5.50 F SDC	6.00 G	215	820	378	2471	TT	E11-106R-005309
425 / 90 D - 21 (15.00 - 21)	STANDARD	18	11.25		420	1332			TT	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/22/2025 2:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..