

STEER FARM - Technical Specifications



Description

STEER FARM has been designed for 2WD tractors in soil tillage applications, providing excellent steering performance.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: 2WD Tractor

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	105 A8

Dimensions US Standard

Usa code	94065844
Ply Rating	10
Section Width (inch)	8.1
Overall Diameter (inch)	31.7
Static Loaded Radius (inch)	14.9
Rolling Circumference (inch)	96.5
Rim Rec	5.50 F
Rim Alt	5.00 F ; 5 K ; 6.00 F
TRA Code	F2

Load capacity (lbs)

mph / psi	56
25	2040

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 10:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..