

# **STEER GRIP - Data Sheet**



# **Description**

STEER GRIP is the perfect steering-axle fitment for on/off trucks. The wide central rib with straight lugs makes the tire suitable for free rolling applications and provides enhanced grip for excellent performance on both wet and dry conditions off the road. The special tread compound has been designed for combining best wear resistance with cut-and-chip resistance whereas the strong casing ensures an extended tire life-cycle.

#### **UM**

**US Standard** 

### Construction



# Machinery

OTR: On/Off Truck

SIZE	Version	USACode	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Туре	Tread Depth
10.00 - 20	STANDARD	94047024	18	7.5	7.0	11.3	42.7	20.1	129.5	TT	26
11.00 - 20	STANDARD	94052103	18	8.0	7.5	11.8	44.1	20.7	133.7	TT	29
12.00 - 24	STANDARD	94049363	20	8.5	8.0	12.2	49.1	23.1	149	TT	28

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 5/22/2025 5:04 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..