

SUPER SAND - Technical Specifications



Description

SUPER SAND is particularly suitable for trailers operating on sandy surfaces during hot weather conditions. It features high flotation capability and is ideal for all operations requiring a high level of handling.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Trailer

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

Dimensions US Standard

Usa code	94025558
Ply Rating	12
Section Width (inch)	15.2
Overall Diameter (inch)	48.2
Rim Rec	10.00 V
Rim Alt	10.00 W

Load capacity (lbs)

mph / psi	35
40 LS	5205
40 LD	4540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 7:12 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..