

TR 133 - Data Sheet



Description

TR 133 has been specially designed for tractors in soil tillage applications. Thanks to the increased number of lugs, this tire features excellent traction as well as enhanced self-cleaning properties. TR 133 provides an extended tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
13.6 - 38 (14.00 - 38)	STANDARD	94043897	R1	132 A8	10	W 12	W 11	13.8	62.2	28.9	190.7	TT	E11-106R-003549

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 5:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..