

## TR 313 - Data Sheet



### Description

TR 313 is a lawn and garden tire suitable for municipality and soil tillage operations with implement machinery, trenchers and orchard harvesters. The large contact area provides excellent grip. The TR 313 tire has been engineered to ensure a high level of stability also in critical operating conditions along with great self-cleaning properties.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Implement Machinery • Orchard Harvester •  
Trencher

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
31 X 15.50 - 15	STANDARD	94025589	8	13 LB		14.6	30.7	13.5	87.9	TL	E4-106R-002208

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/21/2025 10:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..