

TR 360 - Technical Specifications

Description

TR 360 is suitable for implement machinery in on-and-off-the-road transport as well as lawn and garden applications. The particular tread design along with the casing structure ensures a long tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery



Version	STANDARD
Type	TL
Tyre Size	18 X 7 - 8

Dimensions US Standard

Usa code	94013104
Ply Rating	6
Section Width (inch)	7.1
Overall Diameter (inch)	18.1
Static Loaded Radius (inch)	8
Rolling Circumference (inch)	52.5
Rim Rec	5.5
ECE	E4-106R-002184

Load capacity (lbs)

mph / psi	46
10	990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 9:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..