

TR 387 IND - Data Sheet



Description

TR 387 IND is an industrial tire suitable for industrial trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Compactor • Industrial Tractor • Trailer

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
620/75 - 30 (23.1 - 30)	DUAL BEAD	94065318	R3	157 A8	16	DW 20 A ; DW 20 B		23.8	65.9	30.3	193.3	TL
620/75 - 30 (23.1 - 30)	DUAL BEAD HD	94065325	R3	160 A8	18	DW 20 A ; DW 20 B		23.8	65.9	0	0	TL
24.5 - 32	DUAL BEAD HD	94057702	R3	160 A8	16	DH 21	DH 21 B ; DH 21 H ; DH 21 HB	24.6	69.1	31.1	205.7	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 9:30 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..