

XL GRIP IND3 (RTG) - Data Sheet



Description

XL GRIP (IND-3) is a bias-ply tire for RTG cranes in stacking and lifting applications. The tire features a strong casing made of a specially formulated tread compound, which provides an extended tire life-cycle.

UM

International Standard

Construction

Machinery Industrial: RTG Crane

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	ow	OD	SLR	RC	Туре
16.00 - 25	INDUSTRIAL	IND3	32	11.25/2.0	13.00/2.0	465	1485	682	4395	TL
18.00 - 25	INDUSTRIAL	IND3	40	13.00/2.5	15.00/2.5	510	1615	739	4780	TL
18.00 - 25	INDUSTRIAL	IND3	32	13.00/2.5	15.00/2.5	510	1615	739	4780	TL
21.00 - 25	INDUSTRIAL	IND3	32	15.00/3.0	17.00/3.0	576	1750	789	5185	TL
21.00 - 25	INDUSTRIAL	IND3	36	15.00/3.0	17.00/3.0	576	1750	789	5185	TL
21.00 - 25	INDUSTRIAL	IND3	40	15.00/3.0	17.00/3.0	576	1750	789	5185	TL
21.00 - 25	INDUSTRIAL	IND3	44	15.00/3.0	17.00/3.0	576	1750	789	5185	TL
24.00 - 29	INDUSTRIAL	IND3	42	17.00/3.5		656	1994	900	5860	TL
21.00 - 35	INDUSTRIAL	IND3	40	15.00/3.0		580	2020	928	5980	TL
21.00 - 35	INDUSTRIAL	IND3	36	15.00/3.0		580	2020	928	5980	TL
24.00 - 35	INDUSTRIAL	IND3	48	17.00/3.5		655	2130	975	6302	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 7:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..