

# XL GRIP ULTRA - Technical Specifications



## Description

XL GRIP ULTRA is a bias-ply tire, particularly suitable for on/off trucks in heavy-duty service conditions such as mining applications, quarries and construction sites. The non-directional tread design provides excellent front and lateral traction. The tire features a strong nylon casing with optimized tie bars and a special tread compound to ensure high cut and puncture resistance as well as excellent durability and wear resistance in addition to best self-cleaning properties even on rocky surfaces.

## UM

US Standard

## Construction

 BIAS

## Machinery

OTR: On/Off Truck

Version	STANDARD
Type	TT
Tyre Size	11.00 - 20

## Dimensions US Standard

Usa code	94064212
Ply Rating	18
Overall Width (inch)	11.7
Overall Diameter (inch)	43.9
Static Loaded Radius (inch)	20.8
Rolling Circumference (inch)	132.6
Rim Rec	8.0
Rim Alt	7.5
Tread Depth	31

## Load capacity (lbs)

mph / psi	110
55 LS/LD	6610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 7:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..