

## AGRI GRIP - Specifiche tecniche



### Description

AGRI GRIP è uno pneumatico per le operazioni di trasporto ed è particolarmente idoneo per applicazioni con rimorchi per la canna da zucchero. AGRI GRIP è dotato di una carcassa robusta che offre elevata capacità di carico insieme ad eccellente resistenza a tagli e lacerazioni. Il particolare disegno del battistrada assicura una vita di servizio prolungata.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Rimorchio

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26

## Dimensions International Standard

Ply Rating	18
Overall Width (mm)	595
Overall Diameter (mm)	1560
Static Loaded Radius (mm)	708
Rolling Circumference (mm)	4658
Rim Rec	DW 20 B

## Load capacity (Kg)

km/h / bar	2.60
30 FR LLV	5600

Printed on 25/04/2024 04:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..