

AGRI GRIP - Specifiche tecniche



Description

AGRI GRIP è uno pneumatico per le operazioni di trasporto ed è particolarmente idoneo per applicazioni con rimorchi per la canna da zucchero. AGRI GRIP è dotato di una carcassa robusta che offre elevata capacità di carico insieme ad eccellente resistenza a tagli e lacerazioni. Il particolare disegno del battistrada assicura una vita di servizio prolungata.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Rimorchio

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26

Dimensions US Standard

Usa code	94045747
Ply Rating	18
Overall Width (inch)	23.4
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.9
Rolling Circumference (inch)	183.4
Rim Rec	DW 20 B

Load capacity (lbs)

mph / psi	38
20 FR LLV	12350

Printed on 25/04/2024 06:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..