

AGRIMAX RT 600 - Specifiche tecniche

Description

AGRIMAX RT 600 è lo pneumatico ideale per manti erbosi e le applicazioni di raccolto e irrorazione. Grazie alla sua ampia area di contatto, AGRIMAX RT 600 garantisce una distribuzione di pressione ottimizzata sul terreno riducendo i danni sul manto erboso e proteggendo il terreno. Grazie alla sua tecnologia a spalla tonda, al tallone rinforzato e al maggior numero di ramponi, lo pneumatico garantisce grande stabilità e trazione.

UM

International Standard

Construction

RADIAL

Machinery

Agricoltura: Mietitrebbia , Spargitore, Trattore



Version	STANDARD
Type	TL
Tyre Size	650/65 R 38
LI/SS	157 D/160 A8

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1811
Static Loaded Radius (mm)	833
Rolling Circumference (mm)	5443
SRI (mm)	875
Rim Rec	DW 20 B
ECE	E11-106R-002990

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	2310	2725	3095	3465	3795	4125
50	2430	2865	3255	3645	3990	4335
40	2520	2970	3375	3780	4140	4500
30	2660	3135	3560	3990	4370	4745
10 LT	3100	3650	4150	4650	5090	5530
10 HT	2660	3135	3560	3990	4370	4745

*** - For 10 Cyc application Inflation pressure to be increased by 0.8 bar.**

Printed on 30/09/2022 19:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..