

## AGRIMAX RT 657 - Specifiche tecniche



### Description

AGRIMAX RT 657 è lo pneumatico ideale per la lavorazione del terreno e per l'utilizzo sulla strada; alcune misure sono anche idonee per la vendemmia. Lo pneumatico assicura un eccellente comfort di guida nonché risparmi significativi di carburante. Agrimax RT 657 è la scelta migliore per chi ha bisogno di uno pneumatico versatile e affidabile senza compromettere le performance.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Trattore • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	340/65 R 18
LI/SS	113 A8/B

## Dimensions International Standard

Section Width (mm)	343
Overall Diameter (mm)	899
Static Loaded Radius (mm)	400
Rolling Circumference (mm)	2667
SRI (mm)	425
Rim Rec	W 11
Rim Alt	W 10 ; W 12
ECE	E4-106R-001816
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	645	760	865	970	1060	1150
40	645	760	865	970	1060	1150
30	695	820	930	1040	1140	1235
10 LT	870	1020	1160	1300	1425	1545
10 HT	695	820	930	1040	1140	1235

Printed on 12/04/2024 18:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..