

## AGRIMAX RT 657 - Specifiche tecniche



### Description

AGRIMAX RT 657 è lo pneumatico ideale per la lavorazione del terreno e per l'utilizzo sulla strada; alcune misure sono anche idonee per la vendemmia. Lo pneumatico assicura un eccellente comfort di guida nonché risparmi significativi di carburante. Agrimax RT 657 è la scelta migliore per chi ha bisogno di uno pneumatico versatile e affidabile senza compromettere le performance.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Trattore • Vendemmiatrice

Version	SPECIAL
Type	TL
Tyre Size	540/65 R 34
LI/SS	152 D/155 A8

## Dimensions US Standard

Usa code	94062645
TMPH	1
Section Width (inch)	20.9
Overall Diameter (inch)	61.7
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	186.7
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E4-106R-000652
TRA Code	R1W

## Load capacity (lbs)

mph / psi	90	12	15	17	20	23	29	35
40	3760	4390	4940	5480	6030	6500	7210	7850
30	3960	4610	5180	5760	6340	6830	7570	8220
25	4100	4780	5390	5990	6580	7100	7860	8540
20	4330	5050	5680	6300	6940	7480	8290	9010
5 LT	5040	5890	6610	7350	8090	8720	9660	10490
5 HT	4330	5050	5680	6300	6940	7480	8290	9010

Printed on 12/04/2024 15:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..