

AGRIMAX RT 657 - Specifiche tecniche



Description

AGRIMAX RT 657 è lo pneumatico ideale per la lavorazione del terreno e per l'utilizzo sulla strada; alcune misure sono anche idonee per la vendemmia. Lo pneumatico assicura un eccellente comfort di guida nonché risparmi significativi di carburante. Agrimax RT 657 è la scelta migliore per chi ha bisogno di uno pneumatico versatile e affidabile senza compromettere le performance.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	650/65 R 38
LI/SS	178 A8/175 B

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1816
Static Loaded Radius (mm)	827
Rolling Circumference (mm)	5488
SRI (mm)	875
Rim Rec	DW 20 B
Rim Alt	DW 21 B ; DW 23 B
ECE	E11-106R-008886
TRA Code	R1W

Load capacity (Kg)

	km/h / bar	3.5
	50	6900
	40	7500
	30	8030
	25	8330
	10	11250
	Static	17250
	10 LT	10500
	20 LT	9000
	10 HT	8030

Printed on 18/04/2024 22:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..