

AGRIMAX RT 765 - Specifiche tecniche



Description

AGRIMAX RT 765, uno pneumatico della serie 70 di BKT, è ideale per equipaggiare i trattori più moderni impegnati in applicazioni pesanti, quali lavorazioni del terreno, spostamenti su campo e su strada, la vendemmia e irrorazioni. L'ampia area di contatto garantisce la migliore trazione e ottimo comfort su tutte le superfici in qualsiasi momento. Questo pneumatico offre elevate proprietà di autopulitura e assicura una compattazione del suolo ridotta. Sono disponibili due misure dotate di tecnologia con cinture in acciaio.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	420/70 R 24
LI/SS	130 D

Dimensions US Standard

Usa code	94063024
Section Width (inch)	16.5
Overall Diameter (inch)	49.1
Static Loaded Radius (inch)	21.8
Rolling Circumference (inch)	144.9
Rim Rec	W 13
Rim Alt	W 12 ; W 14 L
ECE	E11-106R-005826
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	2300	2690	3060	3440	3810	4190
30	2420	2820	3220	3620	4010	4400
25	2540	2940	3360	3770	4190	4600
20	2660	3090	3530	3960	4390	4820
5 LT	3100	3600	4110	4620	5130	5620
5 HT	2660	3090	3530	3960	4390	4820

Printed on 17/04/2024 05:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..