

AGRIMAX RT 765 - Specifiche tecniche



Description

AGRIMAX RT 765, uno pneumatico della serie 70 di BKT, è ideale per equipaggiare i trattori più moderni impegnati in applicazioni pesanti, quali lavorazioni del terreno, spostamenti su campo e su strada, la vendemmia e irrorazioni. L'ampia area di contatto garantisce la migliore trazione e ottimo comfort su tutte le superfici in qualsiasi momento. Questo pneumatico offre elevate proprietà di autopulitura e assicura una compattazione del suolo ridotta. Sono disponibili due misure dotate di tecnologia con cinture in acciaio.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	480/70 R 30
LI/SS	141 D

Dimensions US Standard

Usa code	94062218
Section Width (inch)	18.9
Overall Diameter (inch)	58.2
Static Loaded Radius (inch)	25.9
Rolling Circumference (inch)	172.1
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-005522
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	3130	3640	4140	4660	5170	5680
30	3280	3820	4350	4890	5430	5960
25	3430	3980	4540	5100	5670	6220
20	3600	4190	4770	5370	5950	6540
5 LT	4200	4880	5570	6250	6930	7620
5 HT	3600	4190	4770	5370	5950	6540

Printed on 17/04/2024 05:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..