

AGRIMAX RT 765 - Specifiche tecniche



Description

AGRIMAX RT 765, uno pneumatico della serie 70 di BKT, è ideale per equipaggiare i trattori più moderni impegnati in applicazioni pesanti, quali lavorazioni del terreno, spostamenti su campo e su strada, la vendemmia e irrorazioni. L'ampia area di contatto garantisce la migliore trazione e ottimo comfort su tutte le superfici in qualsiasi momento. Questo pneumatico offre elevate proprietà di autopulitura e assicura una compattazione del suolo ridotta. Sono disponibili due misure dotate di tecnologia con cinture in acciaio.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	STEEL BELTED
Type	TL
Tyre Size	580/70 R 38
LI/SS	180 D

Dimensions US Standard

Usa code	94038510
Section Width (inch)	22.7
Overall Diameter (inch)	71.9
Static Loaded Radius (inch)	32.3
Rolling Circumference (inch)	216.7
Rim Rec	W 18 L
ECE	E11-106R-005836
TRA Code	R1W

Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58	64	67
40	7010	8540	10870	12080	13230	14260	15280	16250	17170	17640
30	7360	8970	11420	12690	13890	14980	16050	17060	18030	18520
25	7680	9360	11900	13240	14480	15620	16730	17800	18820	19310
20	8070	9830	12500	13900	15210	16410	17570	18690	19750	20280
15	8310	10130	12890	14320	15670	16910	18110	19260	20360	20900

Printed on 17/04/2024 03:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..