

AGRIMAX RT 765 - Specifiche tecniche



Description

AGRIMAX RT 765, uno pneumatico della serie 70 di BKT, è ideale per equipaggiare i trattori più moderni impegnati in applicazioni pesanti, quali lavorazioni del terreno, spostamenti su campo e su strada, la vendemmia e irrorazioni. L'ampia area di contatto garantisce la migliore trazione e ottimo comfort su tutte le superfici in qualsiasi momento. Questo pneumatico offre elevate proprietà di autopulitura e assicura una compattazione del suolo ridotta. Sono disponibili due misure dotate di tecnologia con cinture in acciaio.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	620/70 R 42
LI/SS	160 D

Dimensions International Standard

Section Width (mm)	625
Overall Diameter (mm)	1935
Static Loaded Radius (mm)	876
Rolling Circumference (mm)	5742
SRI (mm)	925
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E11-106R-005835
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	2475	2880	3285	3690	4095	4500
50	2600	3025	3450	3875	4300	4725
40	2715	3160	3600	4045	4490	4930
30	2850	3315	3780	4245	4710	5175
10 LT	3320	3860	4405	4945	5490	6030
10 HT	2850	3315	3780	4245	4710	5175

Printed on 17/04/2024 03:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..