

AGRIMAX RT 765 - Specifiche tecniche



Description

AGRIMAX RT 765, uno pneumatico della serie 70 di BKT, è ideale per equipaggiare i trattori più moderni impegnati in applicazioni pesanti, quali lavorazioni del terreno, spostamenti su campo e su strada, la vendemmia e irrorazioni. L'ampia area di contatto garantisce la migliore trazione e ottimo comfort su tutte le superfici in qualsiasi momento. Questo pneumatico offre elevate proprietà di autopulitura e assicura una compattazione del suolo ridotta. Sono disponibili due misure dotate di tecnologia con cinture in acciaio.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	650/75 R 42
LI/SS	170 D

Dimensions International Standard

Section Width (mm)	655
Overall Diameter (mm)	2043
Static Loaded Radius (mm)	916
Rolling Circumference (mm)	6147
SRI (mm)	975
Rim Rec	DW21B
Rim Alt	DW20B;DW23B
ECE	E11-106R-006402
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2820	3240	3720	4200	4680	5160	5640	6000
50	2965	3405	3910	4410	4915	5420	5925	6300
40	3090	3550	4075	4600	5125	5655	6180	6570
30	3245	3730	4280	4830	5385	5935	6490	6900
10 LT	3780	4345	4985	5630	6275	6915	7560	8040
10 HT	3245	3730	4280	4830	5385	5935	6490	6900

Printed on 17/04/2024 04:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..