

## AGRIMAX RT 855 - Specifiche tecniche



### Description

AGRIMAX RT 855 si distingue per l'eccellente trazione e il comfort. Principalmente sviluppato per la lavorazione del terreno e il trasporto sia su campo che sulla strada, alcune misure sono anche idonee per applicazioni di irrorazione e vendemmia. AGRIMAX RT 855 possiede ottime doti di autopulitura che consentono il rapido cambio dalle operazioni sul campo all'impiego su strada.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	SPECIAL
Type	TL
Tyre Size	320/85 R 38 (12.4 R 38)
LI/SS	143 A8/B

## Dimensions US Standard

Usa code	94047543
Section Width (inch)	13
Overall Diameter (inch)	59.4
Static Loaded Radius (inch)	27.6
Rolling Circumference (inch)	180.3
Rim Rec	W 11
Rim Alt	W 9 ; W 10 ; DW 10
ECE	E4-106R-000781
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	17	23	29	35	41	46	52
30	2170	2520	3310	4030	4390	4700	5110	5530	6000
25	2170	2520	3310	4030	4390	4700	5110	5530	6000
20	2330	2710	3550	4320	4710	5030	5480	5930	6440
5 LT	2910	3390	4440	5400	5890	6290	6860	7420	8060
5 HT	2330	2710	3550	4320	4710	5030	5480	5930	6440

Printed on 23/04/2024 21:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..