

## AGRIMAX RT 855 - Specifiche tecniche



### Description

AGRIMAX RT 855 si distingue per l'eccellente trazione e il comfort. Principalmente sviluppato per la lavorazione del terreno e il trasporto sia su campo che sulla strada, alcune misure sono anche idonee per applicazioni di irrorazione e vendemmia. AGRIMAX RT 855 possiede ottime doti di autopulitura che consentono il rapido cambio dalle operazioni sul campo all'impiego su strada.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	SPECIAL
Type	TL
Tyre Size	340/85 R 38 (13.6 R 38)
LI/SS	133 A8/B

## Dimensions International Standard

Section Width (mm)	353
Overall Diameter (mm)	1543
Static Loaded Radius (mm)	712
Rolling Circumference (mm)	4668
SRI (mm)	750
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000766
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1135	1320	1505	1690	1875	2060
40	1135	1320	1505	1690	1875	2060
30	1215	1415	1610	1810	2010	2205
10 LT	1525	1770	2020	2270	2520	2765
10 HT	1215	1415	1610	1810	2010	2205

Printed on 23/04/2024 23:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..