

AGRIMAX RT 855 - Specifiche tecniche



Description

AGRIMAX RT 855 si distingue per l'eccellente trazione e il comfort. Principalmente sviluppato per la lavorazione del terreno e il trasporto sia su campo che sulla strada, alcune misure sono anche idonee per applicazioni di irrorazione e vendemmia. AGRIMAX RT 855 possiede ottime doti di autopulitura che consentono il rapido cambio dalle operazioni sul campo all'impiego su strada.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

| | |
|-----------|----------------------------|
| Version | SPECIAL |
| Type | TL |
| Tyre Size | 380/85 R 24 (14.9 R 24) |
| LI/SS | 131 A8/B |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Section Width (mm) | 380 |
| Overall Diameter (mm) | 1256 |
| Static Loaded Radius (mm) | 554 |
| Rolling Circumference (mm) | 3720 |
| SRI (mm) | 600 |
| Rim Rec | W 12 |
| Rim Alt | W 11 ; W 13 |
| ECE | E4-106R-000592 |
| TRA Code | R1W |

Load capacity (Kg)

| km/h / bar | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 1075 | 1250 | 1425 | 1600 | 1775 | 1950 |
| 40 | 1075 | 1250 | 1425 | 1600 | 1775 | 1950 |
| 30 | 1150 | 1340 | 1530 | 1715 | 1905 | 2090 |
| 10 LT | 1440 | 1675 | 1910 | 2145 | 2380 | 2615 |
| 10 HT | 1150 | 1340 | 1530 | 1715 | 1905 | 2090 |

Printed on 23/04/2024 21:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..