

AGRIMAX RT 855 - Specifiche tecniche



Description

AGRIMAX RT 855 si distingue per l'eccellente trazione e il comfort. Principalmente sviluppato per la lavorazione del terreno e il trasporto sia su campo che sulla strada, alcune misure sono anche idonee per applicazioni di irrorazione e vendemmia. AGRIMAX RT 855 possiede ottime doti di autopulitura che consentono il rapido cambio dalle operazioni sul campo all'impiego su strada.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	420/85 R 30 (16.9 R 30)
LI/SS	140 A8/B

Dimensions International Standard

Section Width (mm)	438
Overall Diameter (mm)	1475
Static Loaded Radius (mm)	661
Rolling Circumference (mm)	4421
SRI (mm)	700
Rim Rec	W 15 L
Rim Alt	W 13 ; W 14 L
ECE	E4-106R-000654
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1375	1600	1825	2050	2275	2500
40	1375	1600	1825	2050	2275	2500
30	1475	1715	1955	2195	2435	2675
10 LT	1845	2145	2450	2750	3050	3350
10 HT	1475	1715	1955	2195	2435	2675

Printed on 23/04/2024 22:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..