

AGRIMAX RT 855 - Specifiche tecniche



Description

AGRIMAX RT 855 si distingue per l'eccellente trazione e il comfort. Principalmente sviluppato per la lavorazione del terreno e il trasporto sia su campo che sulla strada, alcune misure sono anche idonee per applicazioni di irrorazione e vendemmia. AGRIMAX RT 855 possiede ottime doti di autopulitura che consentono il rapido cambio dalle operazioni sul campo all'impiego su strada.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	SPECIAL
Type	TL
Tyre Size	460/85 R 30 (18.4 R 30)
LI/SS	145 A8/B

Dimensions International Standard

Section Width (mm)	475
Overall Diameter (mm)	1544
Static Loaded Radius (mm)	680
Rolling Circumference (mm)	4562
SRI (mm)	725
Rim Rec	W 16 L
Rim Alt	W 14 L ; W 15 L
ECE	E4-106R-000774
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1595	1860	2120	2380	2640	2900
40	1595	1860	2120	2380	2640	2900
30	1710	1990	2270	2550	2830	3105
10 LT	2140	2490	2840	3190	3540	3890
10 HT	1710	1990	2270	2550	2830	3105

Printed on 23/04/2024 20:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..