

AGRIMAX RT 945 - Specifiche tecniche



Description

AGRIMAX RT 945 è stato particolarmente sviluppato per colture a filari: non danneggia le culture e protegge il raccolto. Inoltre, le straordinarie capacità di auto-pulitura consentono il rapido cambio dalle operazioni sul campo all'utilizzo sulla strada, dove AGRIMAX RT 945 dimostra performance brillanti. La sua carcassa resistente conferisce allo pneumatico ottima stabilità, trazione eccellente nonché durabilità straordinaria.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore

Version	STANDARD
Type	TL
Tyre Size	380/90 R 46 (14.9 R 46)
LI/SS	155 A8/B

Dimensions US Standard

Usa code	94040551
Section Width (inch)	15
Overall Diameter (inch)	72.9
Static Loaded Radius (inch)	33.8
Rolling Circumference (inch)	224.4
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-00797
TRA Code	R1W

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52
30	3940	5050	6150	6760	7260	7950	8540	-
25	3940	5050	6150	6760	7260	7950	8540	-
20	4210	5400	6590	7230	7780	8510	9150	-
5	4620	6030	7310	8720	10010	10390	11540	12820

Printed on 02/02/2023 21:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..