

## AGRIMAX RT 945 - Specifiche tecniche



### Description

AGRIMAX RT 945 è stato particolarmente sviluppato per colture a filari: non danneggia le culture e protegge il raccolto. Inoltre, le straordinarie capacità di auto-pulitura consentono il rapido cambio dalle operazioni sul campo all'utilizzo sulla strada, dove AGRIMAX RT 945 dimostra performance brillanti. La sua carcassa resistente conferisce allo pneumatico ottima stabilità, trazione eccellente nonché durabilità straordinaria.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Macchina irroratrice • Trattore

Version	STANDARD
Type	TL
Tyre Size	380/90 R 50 (14.9 R 50)
LI/SS	160A8/B

## Dimensions US Standard

Usa code	94065479
Section Width (inch)	15.4
Overall Diameter (inch)	76.9
Static Loaded Radius (inch)	36.3
Rolling Circumference (inch)	234.6
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E11-106R-006446
TRA Code	R1W

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	4070	5260	6350	7040	7440	8130	8830	9420	9920	---
25	4070	5260	6350	7040	7440	8130	8830	9420	9920	---
20	4350	5630	6800	7540	7970	8710	9460	10090	10610	---
5	5890	7610	9180	10180	10760	11760	12760	13620	14340	14880

Printed on 02/02/2023 22:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..