

AGRIMAX RT 945 - Specifiche tecniche



Description

AGRIMAX RT 945 è stato particolarmente sviluppato per colture a filari: non danneggia le culture e protegge il raccolto. Inoltre, le straordinarie capacità di auto-pulitura consentono il rapido cambio dalle operazioni sul campo all'utilizzo sulla strada, dove AGRIMAX RT 945 dimostra performance brillanti. La sua carcassa resistente conferisce allo pneumatico ottima stabilità, trazione eccellente nonché durabilità straordinaria.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 420/90 R 30 |
| LI/SS | 147 A8/B |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 418 |
| Overall Diameter (mm) | 1518 |
| Static Loaded Radius (mm) | 684 |
| Rolling Circumference (mm) | 4571 |
| SRI (mm) | 700 |
| Rim Rec | DW13 |
| Rim Alt | W 14 L |
| ECE | E11-106R-006021 |
| TRA Code | R1W |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|
| 50 | 1665 | 2155 | 2645 | 2895 | 3075 |
| 40 | 1665 | 2155 | 2645 | 2895 | 3075 |
| 30 | 1780 | 2310 | 2835 | 3100 | 3295 |
| 10 | 2495 | 3235 | 3970 | 4340 | 4615 |

Printed on 24/04/2024 18:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..