

AGRIMAX RT 955 - Specifiche tecniche



Description

AGRIMAX RT 955 è uno pneumatico radiale BKT ideale per le applicazioni di colture a filari, mentre alcune misure sono anche idonee per irrorazione e vendemmia. Lo speciale disegno del battistrada con spalla arrotondata si traduce in eccellente trazione nonché ottime stabilità e proprietà di autopulitura. Grazie alla carcassa robusta, AGRIMAX RT 955 assicura un'elevata capacità di carico.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	230/95 R 40 (9.5 R 40)
LI/SS	132 A8/B

Dimensions International Standard

Section Width (mm)	228
Overall Diameter (mm)	1454
Static Loaded Radius (mm)	690
Rolling Circumference (mm)	4445
SRI (mm)	700
Rim Rec	W 7
Rim Alt	W 8
ECE	E11-106R-004066
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	820	1060	1280	1420	1500	1640	1780	1900	2000	-
40	820	1060	1280	1420	1500	1640	1780	1900	2000	-
30	880	1135	1370	1520	1605	1755	1905	2035	2140	-
10	930	1170	1440	1710	1980	2040	2280	2520	2760	3000

Printed on 21/04/2024 16:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..