

## AGRIMAX RT 955 - Specifiche tecniche



### Description

AGRIMAX RT 955 è uno pneumatico radiale BKT ideale per le applicazioni di colture a filari, mentre alcune misure sono anche idonee per irrorazione e vendemmia. Lo speciale disegno del battistrada con spalla arrotondata si traduce in eccellente trazione nonché ottime stabilità e proprietà di autopulitura. Grazie alla carcassa robusta, AGRIMAX RT 955 assicura un'elevata capacità di carico.

### UM

US Standard

### Construction

RADIAL

### Machinery

Agricoltura: Macchina irroratrice, Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	270/95 R 36 (11.2 R 36)
LI/SS	139 A8/B

### Dimensions US Standard

Usa code	94027484
Section Width (inch)	10.8
Overall Diameter (inch)	56.2
Static Loaded Radius (inch)	26.2
Rolling Circumference (inch)	172
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000659
TRA Code	R1

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2090	2730	3330	3650	3860	4230	4610	4980	5350	-
25	2090	2730	3330	3650	3860	4230	4610	4980	5350	-
20	2250	2930	3570	3910	4140	4540	4950	5350	5740	-
5	2490	3140	3860	4590	5310	5470	6120	6760	7400	8040

Printed on 30/09/2022 19:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..