

AGRIMAX RT 955 - Specifiche tecniche



Description

AGRIMAX RT 955 è uno pneumatico radiale BKT ideale per le applicazioni di colture a filari, mentre alcune misure sono anche idonee per irrorazione e vendemmia. Lo speciale disegno del battistrada con spalla arrotondata si traduce in eccellente trazione nonché ottime stabilità e proprietà di autopulitura. Grazie alla carcassa robusta, AGRIMAX RT 955 assicura un'elevata capacità di carico.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	270/95 R 44 (11.2 R 44)
LI/SS	142 A8/B

Dimensions US Standard

Usa code	94028146
Section Width (inch)	10.8
Overall Diameter (inch)	64.3
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	196.2
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-00784
TRA Code	R1

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2280	2990	3630	3980	4210	4620	5030	5430	5830	-
25	2280	2990	3630	3980	4210	4620	5030	5430	5830	-
20	2450	3200	3890	4270	4510	4950	5390	5830	6260	-
5	2720	3430	4210	5000	5790	5960	6670	7360	8070	8760

Printed on 20/04/2024 02:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..