

AGRIMAX RT 955 - Specifiche tecniche



Description

AGRIMAX RT 955 è uno pneumatico radiale BKT ideale per le applicazioni di colture a filari, mentre alcune misure sono anche idonee per irrorazione e vendemmia. Lo speciale disegno del battistrada con spalla arrotondata si traduce in eccellente trazione nonché ottime stabilità e proprietà di autopulitura. Grazie alla carcassa robusta, AGRIMAX RT 955 assicura un'elevata capacità di carico.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	340/85 R 46 (13.6 R 46)
LI/SS	150 A8/B

Dimensions US Standard

Usa code	94044726
Section Width (inch)	13.9
Overall Diameter (inch)	68.7
Static Loaded Radius (inch)	32.5
Rolling Circumference (inch)	210.5
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-001828
TRA Code	R1

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
30	3190	4140	5030	5470	5840	6430	6940	7400	-
25	3190	4140	5030	5470	5840	6430	6940	7400	-
20	3410	4430	5380	5850	6250	6880	7430	7900	-
5	4550	5870	7100	7760	8310	9090	9870	10530	11080

Printed on 25/04/2024 09:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..