

## AGRIMAX RT 955 - Scheda tecnica



### Description

AGRIMAX RT 955 è uno pneumatico radiale BKT ideale per le applicazioni di colture a filari, mentre alcune misure sono anche idonee per irrorazione e vendemmia. Lo speciale disegno del battistrada con spalla arrotondata si traduce in eccellente trazione nonché ottime stabilità e proprietà di autopulitura. Grazie alla carcassa robusta, AGRIMAX RT 955 assicura un'elevata capacità di carico.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Macchina irroratrice • Vendemmiatrice

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>210/90 R 24</b> (8.3 R 24)	STANDARD	R1	107 A8/B	W 7	W 6	214	1010	462	3027	475	TL	E4-106R-001818
<b>210/95 R 28</b> (8.3 R 28)	STANDARD	R1	116 A8/B	W 7	W 6	214	1111	513	3364	525	TL	E4-106R-001819
<b>210/95 R 32</b> (8.3 R 32)	STANDARD	R1	120 A8/B	W 7	W 6	214	1213	571	3703	575	TL	E4-106R-001391
<b>230/95 R 32</b> (9.5 R 32)	STANDARD	R1	128 A8/B	W 7	W 8	228	1251	585	3810	600	TL	E4-106R-000764
<b>270/95 R 32</b> (11.2 R 32)	STANDARD	R1	136 A8/B	W 9	W 8 ; W 10	275	1327	614	4076	625	TL	E4-106R-000776
<b>230/95 R 36</b> (9.5 R 36)	STANDARD	R1	130 A8/B	W 8	W 7	238	1352	639	4112	650	TL	E4-106R-000765
<b>270/80 R 36</b>	STANDARD	R1	134 A8/B	W 9	W 8; W 10	275	1346	629	4090	650	TL	E11-106R-006758
<b>270/95 R 36</b> (11.2 R 36)	STANDARD	R1	139 A8/B	W 9	W 8 ; W 10	275	1428	665	4335	675	TL	E4-106R-000659
<b>270/95 R 38</b> (11.2 R 38)	STANDARD	R1	140 A8/B	W 9	W 8 ; W 10	275	1479	697	4510	700	TL	E4-106R-000657
<b>230/95 R 40</b> (9.5 R 40)	STANDARD	R1	132 A8/B	W 7	W 8	228	1454	690	4445	700	TL	E11-106R-004066
<b>230/95 R 42</b> (9.5 R 42)	STANDARD	R1	133 A8/B	W 8	W 7	238	1506	714	4595	725	TL	E4-106R-000772
<b>300/85 R 42</b> (11.2 R 42)	STANDARD	R1	144 A8/B	W 9	W 10 ; W 11	295	1577	745	4850	750	TL	E4-106R-001396
<b>210/95 R 44</b> (8.3 R 44)	STANDARD	R1	120 A8/B	W 7	W 6	214	1518	721	4653	725	TL	E4-106R-000771
<b>230/95 R 44</b> (9.5 R 44)	STANDARD	R1	134 A8/B	W 8	W 7	238	1556	739	4788	750	TL	E4-106R-000777
<b>270/95 R 44</b> (11.2 R 44)	STANDARD	R1	142 A8/B	W 9	W 8 ; W 10	275	1632	764	4983	775	TL	E4-106R-00784
<b>270/95 R 46</b> (11.2 R 46)	STANDARD	R1	143 A8/B	W 9	W 8 ; W 10	275	1683	792	5169	800	TL	E4-106R-000785
<b>300/95 R 46</b> (12.4 R 46)	STANDARD	R1	148 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1738	812	5318	825	TL	E4-106R-000790
<b>340/85 R 46</b> (13.6 R 46)	STANDARD	R1	150 A8/B	W 12	W 11	353	1746	826	5346	850	TL	E4-106R-001828
<b>230/95 R 48</b> (9.5 R 48)	STANDARD	R1	136 A8/B	W 8	W 7	238	1656	792	5085	825	TL	E4-106R-000778
<b>230/95 R 48</b> (9.5 R 48)	STANDARD	R1	136D/139A8	W 8	W 7	238	1656	792	5085	825	TL	E11-106R-004067
<b>270/95 R 48</b> (11.2 R 48)	STANDARD	R1	144 A8/B	W 9	W 8 ; W 10	275	1733	820	5351	825	TL	E4-106R-000782
<b>340/85 R 48</b> (13.6 R 48)	STANDARD	R1	151D/154A8	W 12	W 11	353	1797	855	5572	875	TL	E11-106R-005765
<b>340/85 R 48</b>	STANDARD	R1	152 A8/B	W 12	W 11	353	1797	855	5572	875	TL	E4-106R-000800

<b>(13.6 R 48)</b>												
<b>300/95 R</b> <b>52</b> <b>(12.4 R 52)</b>	STANDARD	R1	151 A8/B	W9	W 10 ; W 11 ; DW 10 ; DW 11	295	1891	889	5774	900	TL	E4-106R-001484
<b>270/95 R</b> <b>54</b> <b>(11.2 R 54)</b>												
	STANDARD	R1	146 A8/B	W9	W 8 ; W 10	275	1885	894	5815	900	TL	E4-106R-001410

Printed on 21/04/2024 16:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..