

AGRIMAX SPARGO - Specifiche tecniche



Description

AGRIMAX SPARGO è lo pneumatico BKT specifico per applicazioni nelle colture in filari, progettato per aumentare la produttività del campo conservando il suolo nel lungo termine. Dotato di tecnologia VF, lo pneumatico offre una maggiore capacità di carico con gonfiaggio standard. Grazie alla carcassa robusta e il maggior numero di ramponi, AGRIMAX SPARGO garantisce eccellente durabilità abbinata ad una forte stabilità sia sul campo che durante gli spostamenti su strada.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice

Version	STANDARD
Type	TL
Tyre Size	VF 480/80 R 50
LI/SS	179 D

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	2038
Static Loaded Radius (mm)	947
Rolling Circumference (mm)	6224
SRI (mm)	975
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-004757
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
70	3945	4370	4790	5005	5285	5425	5565	5850	6130	6345	6625	6835	7050
From 65 to 40	4340	4805	5270	5500	5810	5965	6120	6430	6740	6975	7285	7515	7750
30	4425	4900	5375	5610	5925	6085	6240	6560	6875	7110	7430	7665	7905
20	4510	4995	5480	5720	6045	6205	6365	6685	7010	7250	7575	7815	8060
10	4770	5285	5795	6050	6390	6560	6730	7075	7415	7670	8010	8265	8525

Printed on 19/04/2024 04:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..