

AGRIMAX SPARGO - Specifiche tecniche



Description

AGRIMAX SPARGO è lo pneumatico BKT specifico per applicazioni nelle colture in filari, progettato per aumentare la produttività del campo conservando il suolo nel lungo termine. Dotato di tecnologia VF, lo pneumatico offre una maggiore capacità di carico con gonfiaggio standard. Grazie alla carcassa robusta e il maggior numero di ramponi, AGRIMAX SPARGO garantisce eccellente durabilità abbinata ad una forte stabilità sia sul campo che durante gli spostamenti su strada.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice

Version	STANDARD
Type	TL
Tyre Size	VF 480/95 R 50
LI/SS	181 D

Dimensions US Standard

Usa code	94075638
Section Width (inch)	18.9
Overall Diameter (inch)	85.9
Static Loaded Radius (inch)	39
Rolling Circumference (inch)	260.1
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-0010083
TRA Code	R1

Load capacity (lbs)

mph / psi	14	17	20	23	26	29	32	35	38	41	44	46
45	8920	9930	11100	12120	12790	13290	13790	14300	14970	15650	16150	16830
From 40 to 25	9650	10730	12010	13100	13830	14370	14920	15470	16200	16920	17460	18190
20	9840	10940	12240	13360	14110	14650	15220	15780	16520	17260	17820	18560
12	10040	11160	12480	13630	14390	14940	15510	16090	16840	17600	18170	18920
5	10610	11800	13200	14410	15220	15800	16410	17010	17810	18610	19220	20010

Printed on 19/04/2024 04:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..