

## AGRIMAX TURF RT 333 - Specifiche tecniche



### Description

AGRIMAX TURF RT 333 (R-3 +) è uno pneumatico radiale progettato per piccoli trattori in applicazioni di giardinaggio, in vigneti e frutteti. Il suo design arrotondato fornisce bassa compattazione del terreno e lo rende estremamente delicato sul terreno. Il suo esclusivo battistrada extra profondo (R-3 +) e il design speciale con blocchi direzionali garantiscono un'eccellente trazione sia sul campo che su strada, nonché un ciclo di vita prolungato. AGRIMAX TURF RT 333 (R-3 +) garantisce grandi proprietà di autopulizia e, grazie alla sua bassa resistenza al rotolamento, consente un notevole risparmio di carburante.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Macchina per il raccolto di frutteti • Trattorino  
• Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	420/85 R 24
LI/SS	137 A8 / 137 B

## Dimensions US Standard

Usa code	94501649
Section Width (inch)	17.1
Overall Diameter (inch)	52.1
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	155.8
Rim Rec	W 15 L
Rim Alt	DW15L;DW14L
ECE	E11-106R-0010344

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2790	3260	3710	4170	4620	5080
25	2790	3260	3710	4170	4620	5080
20	3000	3490	3970	4470	4950	5440
5 LT	3750	4360	4980	5580	6200	6810
5 HT	3000	3490	3970	4470	4950	5440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/05/2025 17:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..