AGRIMAX V-FLECTO - Specifiche tecniche

Description

AGRIMAX V-FLECTO è la risposta di BKT all'impegnativa domanda sia in termini di tecnologia che di performance per i trattori ad alta potenza. Questo pneumatico è perfetto per la lavorazione del terreno e le applicazioni di trasporto garantendo una ridotta compattazione del suolo e eccellenti proprietà di autopulitura. Grazie all'esclusiva tecnologia VF, AGRIMAX V-FLECTO è in grado di trasportare carichi pesanti con una pressione di gonfiaggio inferiore rispetto agli pneumatici standard e IF, raggiungendo velocità elevate. Lo pneumatico si distingue per la Narrow Rim Option (NRO) che consente il montaggio di cerchi standard. BKT ha progettato questo pneumatico con geometria ottimizzata al fine di migliorare il comfort di guida sia su campo che su strada, riducendo il consumo di carburante.

UM

International Standard

Construction

RADIAL

Machinery

Agricoltura: Trattore a elevata potenza

Version	STANDARD
Type	TL
Tyre Size	VF 600/65 R 34 NRO
LI/SS	169 D

Dimensions International Standard

Section Width (mm)	597
Overall Diameter (mm)	1644
Static Loaded Radius (mm)	731
Rolling Circumference (mm)	4952
SRI (mm)	775
Rim Rec	DW 21 B
Rim Alt	DW 20 B
Narrow Rim option	DW 18 L
ECE	E11-106R-007603
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.8	2.0	2.4
70	2430	2800	3220	3590	4010	4380	4910	5275
From 65 to 40	2670	3075	3540	3945	4410	4815	5395	5800
30	2725	3135	3610	4025	4500	4910	5505	5915
20	2775	3200	3680	4105	4585	5005	5610	6030
10	2935	3385	3895	4340	4850	5300	5935	6380
***Upto 10 Cyc with front loader**	3740	4305	4955	5525	6175	6740	7555	8120
10 HT	2725	3135	3610	4025	4500	4910	5505	5915

*** *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.**

Printed on 27/04/2024 02:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..