

AIROMAX AM 27 - Specifiche tecniche



Description

AIROMAX AM 27 è uno pneumatico per l'impiego principalmente su strada, ideale per le applicazioni con gru nel settore costruzioni. Lo pneumatico si distingue per la resistenza al calore e l'eccezionale comfort. AIROMAX AM 27 è uno pneumatico ad alta velocità particolarmente idoneo per tutte le operazioni che richiedono un elevato livello di manovrabilità.

UM

International Standard

Construction

 RADIAL

Machinery

Industriale: Gru mobile

Version	STANDARD
Type	TT
Tyre Size	385/95 R 24 (14.00 R 24)
LI/SS	170 F

Dimensions International Standard

Overall Width (mm)	372
Overall Diameter (mm)	1363
Static Loaded Radius (mm)	626
Rolling Circumference (mm)	4175
Rim Rec	10.00W
ECE	E11-54R-0015910

Load capacity (Kg)

km/h / bar	9.00
80	6000

Printed on 22/02/2024 19:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..