

## AIROMAX AM 27 - Scheda tecnica



### Description

AIROMAX AM 27 è uno pneumatico per l'impiego principalmente su strada, ideale per le applicazioni con gru nel settore costruzioni. Lo pneumatico si distingue per la resistenza al calore e l'eccezionale comfort. AIROMAX AM 27 è uno pneumatico ad alta velocità particolarmente idoneo per tutte le operazioni che richiedono un elevato livello di manovrabilità.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industriale: Gru mobile

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
<b>385/95 R 24</b> <b>(14.00 R 24)</b>	STANDARD	170 F	10.00W		372	1363	626	4175	TT	E11-54R-0015910
<b>385/95 R 25</b> <b>(14.00 R 25)</b>	STANDARD	170 F	10.00/1.5		372	1363	626	4175	TL	E11-54R-0015911
<b>445/95 R 25</b> <b>(16.00 R 25)</b>	STANDARD	174 F	11.25/2.0	11.00/1.7 CR ; 11.00/1.7CRL	440	1490	695	4587	TL	E4-54R-0028867
<b>505/95 R 25</b> <b>(18.00 R 25)</b>	STANDARD	186 E	13.00/2.5		492	1600	728	4900	TL	
<b>525/80 R 25</b> <b>(20.5 R 25)</b>	STANDARD	176 F	17.00/2.0	17.00/1.7 CR	530	1481	681	4534	TL	E11-54R-0016681

Printed on 26/02/2024 02:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..