

AIROMAX AM 543 - Specifiche tecniche



Description

AIROMAX AM 543 è lo pneumatico ideale per applicazioni con gru nel settore costruzioni. Lo pneumatico mostra eccellente trazione insieme ad elevata stabilità. Visto che gli pneumatici per gru sono soggetti a sollecitazioni e condizioni d'impiego estreme, AIROMAX AM 543 è stato progettato per fornire un'ottima resistenza al calore. Inoltre, è idoneo per tutte le operazioni in cui si richiede un elevato livello di manovrabilità.

UM

US Standard

Construction

 RADIAL

Machinery

Industriale: Gru mobile

Version	STANDARD
Type	TL
Tyre Size	385/95 R 25 (14.00 R 25)
LI/SS	170 E

Dimensions US Standard

Usa code	94064519
Overall Width (inch)	14.8
Overall Diameter (inch)	53.3
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	163.6
Rim Rec	10.00/1.5

Load capacity (lbs)

mph / psi	130
43	13200

Printed on 26/04/2024 18:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..