

## AIROMAX AM 543 - Scheda tecnica



### Description

AIROMAX AM 543 è lo pneumatico ideale per applicazioni con gru nel settore costruzioni. Lo pneumatico mostra eccellente trazione insieme ad elevata stabilità. Visto che gli pneumatici per gru sono soggetti a sollecitazioni e condizioni d'impiego estreme, AIROMAX AM 543 è stato progettato per fornire un'ottima resistenza al calore. Inoltre, è idoneo per tutte le operazioni in cui si richiede un elevato livello di manovrabilità.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industriale: Gru mobile

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
<b>385/95 R 24</b> <b>(14.00 R 24)</b>	STANDARD	170 E	10.00W		375	1355	627	4156	TT
<b>385/95 R 25</b> <b>(14.00 R 25)</b>	STANDARD	170 E	10.00/1.5		375	1355	627	4156	TL
<b>445/95 R 25</b> <b>(16.00 R 25)</b>	STANDARD	177 E	11.25/2.0	11.00/1.7 CR ; 11.00/1.7CRL	435	1480	670	4502	TL

Printed on 26/04/2024 21:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..