

AS 2001 - Specifiche tecniche



Description

AS 2001 è uno pneumatico diagonale a tele incrociate, molto idoneo per trattori nelle operazioni per la lavorazione del terreno. Il disegno garantisce eccellente trazione e ottime proprietà di autopulitura. AS 2001 è realizzato con una miscela particolarmente resistente a tagli e lacerazioni che assicura anche elevata capacità di carico.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	18.4 - 26
LI/SS	138 A8

Dimensions US Standard

Usa code	94002740
Ply Rating	10
Section Width (inch)	18.4
Overall Diameter (inch)	58.1
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	167.3
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-003367
TRA Code	R1

Load capacity (lbs)

mph / psi	26
25	5200

Printed on 27/04/2024 09:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..