AS 504 - Specifiche tecniche

Description

AS 504 è uno pneumatico agro-industriale principalmente sviluppato per le operazioni di lavorazioni della terra, attrezzi agricoli e movimentazione di materiali. Questo pneumatico che si distingue per le eccellenti proprietà di autopulitura e il grip potenziato, è ideale per rimorchi e sollevatori telescopici. AS 504 è disponibile in diverse versioni al fine di soddisfare le esigenze specifiche dell'utilizzatore: una versione “HD” con mescola speciale resistente a tagli e lacerazioni, mentre la versione “special” è dotata di una carcassa rinforzata che assicura una vita prolungata dello pneumatico.

UM

US Standard

Construction

BIAS

Machinery

Agricoltura: Sollevatore telescopico • Rimorchio da campo
Industriale: Sollevatore telescopico

Version	STANDARD
Type	TL
Tyre Size	19.0/45 - 17
LI/SS DRIVE WHEEL	134 A8
LI/SS FREE ROLLING	147 A8

Dimensions US Standard

Usa code	94064465
Ply Rating	16
Section Width (inch)	18.3
Overall Diameter (inch)	34.1
Static Loaded Radius (inch)	15.3
Rolling Circumference (inch)	101.5
Rim Rec	16.00
ECE	E11-106R-006179

Load capacity (lbs)

mph / psi	45
5 FR	9520
15 FR	8090
20 FR	7615
25 FR	6800
5 DW	6550
15 DW	5570
20 DW	5240
25 DW	4680

Printed on 24/04/2024 06:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..