

AS 507 - Specifiche tecniche



Description

AS 507 è stato progettato per le lavorazioni della terra con rimorchi e attrezzi agricoli. Lo pneumatico si distingue per le sue ottime proprietà di autopulitura oltre alla maggiore trazione sul terreno.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	185/65 - 15
LI/SS DRIVE WHEEL	76 A8
LI/SS FREE ROLLING	89 A8

Dimensions International Standard

Ply Rating	4
Section Width (mm)	185
Overall Diameter (mm)	640
Static Loaded Radius (mm)	301
Rolling Circumference (mm)	1894
Rim Rec	5½ J
ECE	E4-106R-002185

Load capacity (Kg)

	km/h / bar	2.80
	10 FR	810
	25 FR	690
	30 FR	650
	40 FR	580
	10 DW	560
	25 DW	475
	30 DW	450
	40 DW	400

Printed on 24/04/2024 09:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..